

2641 Schaeffer Dr S.W. • Cedar Rapids, IA. 52404 • Phone 319-721-6553 • Fax 319-247-4773 • inlinesolutionsinc@gmail.com

STUBBY (TIPPING) TABLE



24" OR 30" WIDE TABLE

SPECIFICATIONS:

- WIDTH: 24" OR 30"
- LENGTH: 70.5" LONG
- HEIGHT: Minimum 27"
 - Maximum 38"
- SPEED: Maximum 150 FEET Per Min
- POWER: 3 PHASE, 220V 20 AMP
- MOTOR AC INVERTER DRIVE 24VDC CONTROLS
 - 24" WIDTH INCLUDES (2) VACUUM BELT LINES 1.75" WIDE
 - 30" WIDTH INCLUDES (3) VACUUM BELT LINES 1.75" WIDE
 - SELF POWERED JL INTEGRATED NIC 04 ELECTRICAL
 - OPTION FOR MBO INTEGRATION (24 PIN ONLY)
 - HIGH VOLUME BLOWER
 - COGGED BELT DRIVE
 - CRIB RAILS FOR FEEDER ATTACHMENT
 - 1 CROSS BAR WITH NIP WHEELS
 - FULL VACUUM CONTROL ON INDIVIDUAL CHAMBERS
 - SIMPLE "TOOL LESS" ADJUSTMENT OF VACUUM CHAMBERS FOR BELT POSITIONING
 - HEX SHAFT AXEL DRIVE FOR EASY ADJUSTMENT AND POSITIVE DRIVE
 - Purpose; A SHORT LENGTH TABLE FOR TIPPING OR PLOWING OR WHEN ADDITIONAL LENGTH IS NEED WHEN USING OTHER JL EQUIPMENT

Systems, Solutions, Satisfaction and Support